

TECHNICAL SPECIFICATION

Power supply : 3P 380V 50Hz 1200W.

Machine dimensions: L2000mmxW1100mmxH (Table height+1300mm).

Machine weight : 820kg.

Working height: 550mm~750mm (adjustable).

Conveyor speed : 19M/min.

Carton dimensions: L(250~500)mm,W(200~450)mm, H(150~400)mm.

Adhesive tape spec : 48~72mm.

Adhesive tape material : kraft paper,or,BOPP.

Air pressure : 5~6kgf/cm².

Electric&pneumatic components:

- * **Contactor :** France "Schneider".
- * **Pushbutton switch :** France "Schneider".
- * **PLC:** Germany "Siemens".
- * **HMI:** China "Meiwa".
- * **Motor :** Taiwan "CPG".
- * **Pneumatic components :** Taiwan "Airtac".
- * **Other :** France "TE" and other famous brand switch.

Working noise : ≤75DB.

Room temperature : 0~40°C.



Tecnipac, Inc.
2534 State Street #444
San Diego, CA 92101 USA
TEL. (707) 361 68 29
jmarin19@hotmail.com
www.tecnipacinc.com

Machine Feature :

Automatic adjustment for different carton width and height.

Side belts drive.

Automatically fold carton top flaps.

Automatically convey and seal the carton box.

Suitable to connect full automatic production line.



FULL AUTOMATIC CASE SEALER MODELO TMH-FJ-3B

PHARMACEUTICAL CONFECTIONERY FOOD AUTOMOTIVE ELECTRONICS WINE CHEMISTRY MEAT SAUSAGE DAIRY PRODUCTS COSMETICS CLEANING AGRICULTURE BEVERAGE



GUADALAJARA, JAL.
TEL. (33) 3777 - 1730
FAX. (33) 3777 - 1739
ventasgdl@empac.com.mx

MÉXICO, D.F.
TEL. (55) 2291 - 0962
FAX. (55) 2291 - 1378
empacdf@empac.com.mx

MONTERREY, N.L.
TEL. (81) 8311 - 2500
FAX. (81) 8327 - 7151
empacmtty@empac.com.mx

GRUPO EMPAC, S.A. DE C.V.
CREAMOS SOLUCIONES INNOVADORAS EN
AUTOMATIZACIÓN PARA LA INDUSTRIA

www.empac.com